



Type:	57033	Systems to charge:	Ni-MH
Designation:.....	Mobile Charger	Cell sizes:.....	AAA, AA
		Cell Configurations:.....	AAA, AA, 2 / 4 pcs.

Dimensions:	Charger:	Car-Adapter:
Lenght:.....	111 ± 0.5 mm	915 ± 5 mm
Widht:.....	73 ± 0.5 mm	35 ± 1 mm
Height:.....	30 ± 0.5 mm	13.8 ± 1 mm
Weight:.....	123g	32 g

Charging methods:	Charge:	Maintenance Charge:
AA:.....	Current: 700mA ± 50mA	Current: 50 ± 5mA
AAA:.....	Current: 350m A ± 50mA	Current: 25 ± 5mA

Housing:	Indications: 1 LED
Housing Material:.....	PC6485
Casing color:.....	Black
Cover color:.....	Black
	AAA, AA,cell mix:..... Red LED flash= Charge
	AAA, AA,cell mix:..... Red LED ON = Trickle Charge
	AAA,, AA,cell mix:..... LED OFF = fault mode or No battery

Cut off criteria:	Power:
NiMH / Standard cells:.....	Timer: 4 hours,
- delta V:	-10mV
Temperature Protection:	55 +/-5°C
	Primary:..... 100-240 VAC 50/60 Hz 7,5W 12V DC 500 mA
	Secondary: 2.8V/5.6V

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries