

Declaration of Performance (DoP)

DoP Number: DOP-UNOVIA-MS_30-2026

Trade name: Unovia[®] MS 30 POLYMER CONSTRUCT

Manufacturer / Importer: Floorweb B.V., Taanderstraat 13, 2222 BG Katwijk, The Netherlands

Harmonised Standard: EN 15651-1 :2012

Notified body/ies: 1292 – FUNDACION TECNALIA RESEARCH & INNOVATION

1. Unique identification code of the product-type

UNOVIA[®] MS 30 CONSTRUCT

2. Intended use/uses

Sealant for joints on the external an internal side of façade elements (intended for use in cold climates: -30°C):
acoustic EN 15651-1; type F-EXT-INT-CC, class 20HM.

3. Declared performance

Test item	Reference Standard	Test result
Reaction to fire	EN 13501-1:2007 + A1:2010	Class F
Release of chemicals dangerous to the environment and health :	EN 15651-1 :2012	See product safety data sheet
Water tightness and air tightness as determined by :		
Resistance to flow (EN ISO 7390)	EN 15651-1 :2012	≤ 3 mm
Loss of volume (EN ISO 10563)	EN 15651-1 :2012	≤ 10 %
Tensile properties (i.e. at maintained extension) at -30°C (modif. EN ISO 8340)	EN 15651-1 :2012	NF
Tensile properties at maintained extension after water immersion (EN ISO 10590)	EN 15651-1 :2012	NF
Durability Conditioning: Method A / NF = No Failure Substrates: Anodized aluminium and mortar M2 substrates, without primer.	EN 15651-1 :2012	PASS

The performance of the product described above is in conformity with the declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Naam : Arjan Hogewoning
Plaats : Katwijk
Datum : 24-02-2026
Handtekening :

