

1370

1200

85

60

25

60

25

85





770

600

23,61" X 47,24"

PORCELÁNICO-PORCELAIN TILES  
RECTIFICADO - RECTIFIED -

60x120 cm




MODEL / MODELO **DINAMARCA NUEZ**  
QUALITY / CUALIDAD **1**  
OPERATOR/OPERARIO **4** PEJASCA **2** Baldosas prensadas en seco,  
CALIBER / CALIBRE **5** METROSCA **2** ISO 13006 (2018), Anexo G  
Shade / TONO: hout Bla, M 120x60 cm  
W (1200mm x 600mm x250mm) GL  
1er choix  
**GLAZED - GL**



Table with technical specifications in multiple languages, including material type, dimensions, and manufacturer information.

ISO 13006 - EN 14411  
AN. G Group Bla/GL  
41431046

DO NOT DRY CUT USING MOTORIZED EQUIPMENT DUE TO THE POTENTIAL FOR EXPOSURE TO HARMFUL SILICA DUST. USE OF A WEY SAW OR A SCORE & SNAP TOOL WHEN CUTTING IS NECESSARY DURING THE INSTALLATION PROCESS.



PORCELÁNICO / PORCELAIN TILE  
120 cm x 60 cm  
23,61" X 47,24"  
GLAZED PORCELEIN



Table with technical specifications and CE mark, including material type, dimensions, and manufacturer information.

Contact:  
New Tiles  
Carretera Castellón 19  
ESP-12110 Alcora (Castellón)  
info@new-tiles.com

EL INHERENTE A LA PRODUCCIÓN DE CIELOS PORCELÁNICO EMBAJADO UNA CERTA VARIACIÓN DE TONOS...

A CERTAIN VARIATION IN THE SHADE IS AN INHERENT FEATURE OF PORCELAIN TILE PRODUCTION...

UNE CERTAIN VARIATION DANS LE TON EST INHÉRENTE AU PROCÈS DE FABRICATION DE MOYENNE ÉCHELLE...

DEINE CERTAIN VARIATION IN DER FARBE IST EIN ERGEBNIS DER HERSTELLUNG VON QUALITÄTSPRODUKTEN...

"Las baldosas cerámicas una vez que llegan al final de su vida útil son un residuo inerte, que para su correcta gestión debe ser entregado a un gestor autorizado de residuos, favoreciendo su reciclado"

"Ceramic tiles, once they reach the end of their useful life, are an inert waste, which for its correct management must be delivered to an authorized waste manager, favoring their recycling"

"Les baldosas cerámicas una vez que llegan al final de su vida útil son un residuo inerte, que para su correcta gestión debe ser entregado a un gestor autorizado de residuos, favoreciendo su reciclado"

"Ceramic tiles, once they reach the end of their useful life, are an inert waste, which for its correct management must be delivered to an authorized waste manager, favoring their recycling"

Para productos SIN RECTIFICAR como RECTIFICADOS, es aconsejable la utilización de una junta de colocación mínima de 1.5mm y 0.5mm respectivamente.

For non-rectified and rectified product, a joint width of at least 1.5mm and 0.5mm respectively is recommended.

Para formatos rectangulares, cuando se colocan a junta trabada, es aconsejable igualmente colocar a 3/4 de pieza.

When staggering rectangular tiles, it is also recommended to stagger them up to a quarter of the length of the tiles in the previous row.

Para baldosas rectangulares, cuando se colocan a junta trabada, es aconsejable igualmente colocar a 3/4 de pieza.

When staggering rectangular tiles, it is also recommended to stagger them up to a quarter of the length of the tiles in the previous row.