1160

1000

85

60

25

60

25

85

1000

1160

39,37" X39,37"

PORCELÁNICO-PORCELAIN TILES

RECTIFICADO - RECTIFIED -

100x100 cm

MODEL / MODELO: **CONCRETE MOKA**

QUALITY / CUALIDAD: 1

OPERATOR/OPERARIO: 4 PIEZAS CAJA 2

CALIBER / CALIBRE: 5 METROS CAJA 2

SHADE / TONO: betonlook

Baldosas prensadas en seco, ISO 13006 (2018), Anexo G
Bla, M 100 cm x 100 cm
W (1000 mm x 1000 mm x 10,2 mm) GL
1ér choix

GLAZED - GL

8 436559 880466

14710/1/N02/5/1764/5443

MANUFACTURER NAME:	
COUNTRY OF ORIGIN: SPAIN	
QUALITY: FIRST CLASS	
DRY PRESSED TILE, SASO ISO 13006:2018, ANNEX G GROUP BIA	BIA, ملحق ج 13006:2018
NOMINAL SIZE: 100 X 100 cm	
WORK SIZE: 1000 mm x 1000 mm x 10 mm	1000 mm x 1000 mm x 10 mm
MODULAR OR NON MODULAR: NO MODULAR	
NATURE OF THE SURFACE: GLAZED (GL)	
ANY SURFACE TREATMENT AFTER FIRING: YES RECTIFIED	
TOTAL NUMBER OF TILES IN THE PACKAGE: 2	
TOTAL DRY WEIGHT FOR TILES 5KGS, NOT ENDED: 48 KG APPROX	
BARCODE NUMBER:	BIA: 8436559674243
SALES SPECIFICATION STANDARD: SASO ISO 13006:2018	SASO ISO 13006:2018

COUNTRY OF ORIGIN:	MADE IN EU
NOMINAL SIZE (CM):	60X120 CM
NATURE OF TILE SURFACE:	GLAZED (GL)
TYPE OF TILE:	WALL & FLOOR TILE
THIS PRODUCT COMPLIES WITH	ISO 13006:2018
NOT MODULAR SIZE /NON MODULAIRE/	

FORMATO NOMINAL
NOMINAL FORMAT
60X120 CM
23.61" X 47.24"

GL
GLASED TILE
BALDOSA ESMALTADA

TRIEZ RÉEMPLOYEZ RECYCLEZ
PLASTIC/ORME ou DISTRIBUTEUR ou DÉCHETTERIE
Adressez sur quefairedemesdechets.fr

ISO 13006 - EN 14411
AN. G Group Bla/GL

41431046

DO NOT DRY CUT USING MOTORIZED EQUIPMENT DUE TO THE POTENTIAL FOR EXPOSURE TO HARMFUL SILICA DUST. USE OF A WET SAW OR A SCORE & SNAP TOOL WHEN CUTTING IS NECESSARY DURING THE INSTALLATION PROCESS.

UK CA

BIa/2021

BS EN 14411

To product ceramic tiles and tile pieces, with a water absorption less of E, tile fixers, for indoor and outdoor wall, floors

Reaction to fire	A1/A1
Breaking strength N	> 1100 N
Adhesion strength, tile strength, type	> 1 N/mm²
Cleavage perpendicular to surface	Complies
Dimensions, characteristics	Complies
Water tightness	Complies
Outdoor use, frost/ice thaw resistance	Complies

SASO QUALITY MARK

اي معالجة تعدّ على السطح بعد عملية الحرق : مقصرص
رقم الانتاج او رقم الدفعة: حسب التسمية منفصلة
رمز اللون و اللون : حسب التسمية منفصلة
عدد البلاط
8436559674243 باركد

Porcelánico / Porcelain Tile
100 cm x 100 cm
39,37" x 39.37" aprox.
GLAZED PORCELAIN

TRIEZ RÉEMPLOYEZ RECYCLEZ
Adressez sur quefairedemesdechets.fr

New Tiles

CE	CARACTERÍSTICAS (CHARACTERISTICS)	VALOR DECLARADO (DECLARED VALUE)
NEW TILES S.L. CARRETERA - CU - 160 KM 16 - VILLAMES - 12192 (CS) Nº 006 EN-14411-2012	Reacción al fuego (Reaction to fire)	A1 / A1
	Fuerza de rotura (Breaking strength)	≥ 1100 N
	Adhesión (Bond strength-adhesion) Adhesivo / cemento (Cementitious adhesives)	(≥0,5 / ≥ 1 N/mm²) (≥0,5 / ≥ 1 N/mm²)
Baldosas cerámicas de prensado en seco, para pavimentos y revestimientos interiores y exteriores	Durabilidad (hielo / deshielo) (Durability for freeze thaw resistance) (interior use) (uso interior) (uso exterior, resistente a la helada) (external use freeze thaw resistance)	CUMPLE PASS CUMPLE PASS
Any physical property tested with water as the liquid phase shall be assessed on samples that have been in contact with water and then dried	Resistencia al choque térmico (Thermal shock resistance)	CUMPLE PASS

Contact:
New Tiles
Carretera Castellón 19
ESP-12110 Alcora (Castellón)
info@new-tiles.com

ES INHERENTE A LA PRODUCCIÓN DE GRES PORCELÁNICO ESMALTADO UNA CIERTA VARIACIÓ DE TONALIDAD.

SE ACONSEJA TENER SEPARADOS PARTIDAS RETIRADAS DE FÁBRICA EN DIFERENTES PERIODOS.

VARIFICAR ANTES DE COLOCAR: TONALIDAD, CALIBRE Y CLASE, NO SE ADMITIRAN RECLAMACIONES REFERENTES AL MATERIAL YA COLOCADO.

EL MATERIAL DEBE CORTARSE EN HÚMEDO.

A CERTAIN VARIATION IN THE SHADE IS AN INHERENT FEATURE OF PORCELAIN TILE PRODUCTION.

WE RECOMMEND HAVING DIFFERENT BATCHES TAKEN FROM THE FACTORY AT DIFFERENT TIMES.

CHECK BEFOR FIXING AS REGARDS SHADE, SIZE AND TYPE, NO COMPLAINTS FOR FIXED MATERIAL WILL BE ACCEPTED.

THIS MATERIAL MUST BE CUT WITH A WET SAW.

UNE CERTAINE VARIATION DANS LE TON EST INHERENTE AU PROCESSUS DE FABRICATION DU REVETEMENT EMAILLE

IL EST CONSEILLE DE CONSTITUER DES LOTS EN FONCTION DES RETRAITS EFFECTUES A LA FABRIQUE A DES PERIODES DIFFERENTES.

VERIFIER AVANT LA POSE: ILE TON, LE CALIBRE ET LE MODELE, AUCUNE RECLAMATION NE SERA ADMISE APRES LES POSE.

LE MATERIEL DOIT ETRE COUPE IMPERATIVEMENT AVEC UNE MACHINE A EAU

EINE GEWISSE FARBABWEICHUNG LIEGT IN DER NATUR DER HERSTELLUNG VON GLASIERTEN FEINSTZEUG IM EINBRANDVERFAHREN.

ES WIRD GERATEN, DIE EINZELNEN LIEFFARTEN NACH LIEFERDATUM GETRENNT ZU LAGERN.

VOR DEM HOLGEN BITTE ÜBERPRÜFEN: FARBTON, FORMAT UND KLASSE, REKLAMATIONEN VON VERLEGTEN MATERIAL WERDEN NICHT ANGENOMMEN.

DIE FLIESEN MUSSEN NASS GESCHNITTEN WERDEN.

"Las baldosas cerámicas una vez que llegan al final de su vida útil son un residuo inerte, que para su correcta gestión debe ser entregado a un gestor autorizado de residuos, favoreciendo su reciclado."

"Ceramic tiles, once they reach the end of their useful life, are an inert waste, which for its correct management must be delivered to an authorized waste manager, favoring their recycling"

Instalación Obligatoria con cuñas autonivelantes.
Installation Obligatoire avec des cales autonivelantes.
Installation Obligatorie avec des cuñas auto-niveladas.

COLOCACIÓN CORRECTA
CORRECT FASHION
الطريقة الصحيحة

COLOCACIÓN INCORRECTA
INCORRECT FASHION
الطريقة الغير صحيحة

Tanto en productos SIN RECTIFICAR como RECTIFICADOS, es aconsejable la utilización de una junta de colocación mínima de 1.5mm and 0.5mm respectivamente is recommended.

Para formatos rectangulares, cosando se colocan a junta trabada, es aconsejable igualmente colocar a 3/4 de pieza.

Both in non-rectified and rectified product, a joint width of at lest 1.5mm and 0.5mm respectively is recommended.

When staggering rectangular tiles, it is also recommended to stagger them up to a quarter of the length of tiles in the previous row.