PREMIUM FOL



PRIMER WATER BASED

GENERAL

Premiumfol Primer water based Is a ready-to-use roller or brush-on white solvent-free primer based on (virtually) unsaponifiable synthetic resin dispersion. The Primer water based is transparent after drying.

Premiumfol Primer water based is suitable for promoting adhesion and acts as an absorption-reducing deep Primer water based for use as pretreatment under cement, lime, gypsum plaster layers , smooth precast concrete, and stony substrates in combination with Premiumfol Adhesive & Sealant, Premiumfol EPDM ZK-Acryl & Premiumfol EPDM ZK-Butyl.

Premiumfol Primer water based is liquid, direct and easy to apply. Min. film formation temperature is 5°C. This applies to both substrate and ambient temperature.
Drying time is approx. 1 hour, depending on substrate, temperature, relative humidity and application. Hardening takes place by drying and polymerisation. Solids content is 23% m/m, volume mass is 1.01 kg/l.

Visit our website for technical information: **www.berdal.com/downloads**

AVAILABILITY

Premiumfol Primer water based is available in the following packaging:

Description	Article Number	EAN Code
Premiumfol Primer water based 1 L	WKFEP400-0075	8713331027791

RELATED PRODUCTS

Description	Article Number	EAN Code
Premiumfol Adhesive & Sealant 290 ml	WKFEP400-0080	8713331027906
Premiumfol EPDM ZK-Acryl	WKFEP400-0008 t/m WKFEP555-0040	-
Premiumfol EPDM ZK-Butyl	WKFEP550-0001 t/m WKFEP550-0004	-

PRODUCT PROPERTIES

Advantages of this Primer water based are:

- ✓ Liquid, instant and easy to apply
- ✓ Dries transparent and therefore does not cause staining

APPLICATION

Transport frost-free and store in original unopened cans at a temperature between 15° and 25°Celsius. Avoid direct sunlight. Shelf life at least 24 months with proper storage. See the BB date ('Best Before date') on the packaging. Premiumfol Primer water based is easy to apply by roller, block brush or brush. Premiumfol Primer water based is ready to use and must not be diluted or mixed with foreign materials. Only apply to dry, load-bearing, oil-, grease-, dirt- and dust-free surfaces. Cover or protect surfaces not to be treated, otherwise clean immediately with clean, warm water.

Consumption is approx. 100-150 ml/m2. In most cases, one application is sufficient. For very weathered and absorbent substrates, a second treatment should be carried out 'wet on wet', until the necessary saturation of the substrate is achieved. Avoid moisture, draughts and direct sunlight during application and binding. Do not apply during (expected) frost. For processing instructions per application, please refer to our detailed processing instructions for Premiumfol.

SAFETY DATA SHEET

For current and detailed information regarding chemical composition, safety aspects, handling, transport, storage and personal protection, etc., please refer to the Safety Data Sheet (SDS) of this product. Your supplier is in possession of the most recent document. You can also request it from Berdal.