



## Technical Data

Category	Article number	Description
Dimmer	6431X	Led Foot Dimmer

Input/ Output		
Rated voltage		230V
Tolerance of the input voltage		+/-10%
Input frequency		50Hz
Input current		0.65A max.
Rated power		150W/VA
Rated power LED		70W
Minimal load for lighting		3W *)
Dimmer principle		R, C (Trailing Edge, Phase cut)
Power consumption		1W

Function		
Overload protection		Thermal fuse 125C
Short-circuit protection		Electronic
Dimming range		5 - 100%
Time for start-up		~ 0.5 sec
Features		Button/slide switch for selection of profile 3 dimming profiles

Shape		
Dimension (mm)		70 x 70 x 32
Weight (g)		60g
Switch		Mechanical push button alternating
Artwork		Tradim logo or OEM on request
Shaft version		4mm shaft metal 6mm adapter

Safety approval		
LVD Safety standard EN 60669-1:2001 2001 + A1:2003 + AC:2007 + A2:2008		✓
EMC Standard EN 60669-2-1:2004 + AC:2007 + A1:2009 + A2:2011		✓
CE/ KEMA KEUR		✓

Remarks		
Lamp can be switched off 100% due to press/turn switch		
Wall dimmer 2495H-KOPP has 3 dimming profiles which can be choosen by button/slide switch		
Indication of active profile on dimmer		

\*) Lower power of led lamps by experiment possible